



MANUFACTURERS OF SPECIALTY CHEMICALS &
INDUSTRIAL AEROSOLS



ISO 9001 :2000 CERTIFIED CO.

**Chem-Verse
Consultants**

(India) Private Ltd.

P.O.Box No.6791, "MAHENDRA MANSION", 167/3, Sion(West),
MUMBAI-400022. INDIA. • Tel:24095503/24033826,
Fax:91-22-24097858 • E.Mail:sales@chemverse.com
www.chemverse.com

PRODUCT BULLETIN

CVC ANTIFREEZE COOLANT

CVC ANTIFREEZE COOLANT maintains optimum radiator temperature even under the most extreme conditions. Under cold temperatures, it prevents freezing of water and in extremely hot environment, it prevents evaporation loss of water thereby maximizing the cooling efficiency. It is non-corrosive and keeps the water channels clean and free from deposits maintaining effective heat transfer. It is ideal for all seasons and for all vehicles.

It may be used neat or diluted with demineralised water for industrial cooling and heat transfer applications such as in radiators, boilers, chilling plants, cooling towers etc. It is an excellent Coolant for Automobiles, Trucks & Diesel Generators.

<u>CHARACTERISITCS</u>		<u>TYPICAL VALUES</u>
1.	Appearance	Green to Yellowish green
2.	Odor	Mild
3.	Specific Gravity	1.01
4.	Refractive index @20°C	1.4320
5.	pH	6.5
6.	Copper strip corrosion @100°C – 3 hrs	ASTM 1a
7.	Pour Point	Below –33°C
8.	Additives	Anti-rust, Anti-corrosive, & Anti-oxidant

Packing: 1-Litre bottle and 25-Litre drum, 200-litre drum.

THE DATA OFFERED HEREIN IS TO BE TREATED AS A GUIDELINE. USER SHOULD THOROUGHLY EVALUATE THE PRODUCT BEFORE STANDARDIZING ITS USE.

{JSD}F:\LITRATUR\ANTIFREZECOLANT\8\99

